

DS-PEA1-21

Panic Alarm Station

DS-PEA1 series panic alarm station is designed with 2 MP HD camera, 2MP HD IR camera and dual network ports. It supports two-way audio. It helps to realize alarm aid the first time and provides more efficient service for building social stability. It is mainly applied to classroom, corridor, laboratory, dormitory, office, hospital, ward and so on.



▪ Key Features

- One-touch emergency calling
- High quality imaging with 2 MP built-in camera
- Real-time security via sound and voice detection
- Supports broadcasting
- Supports dual net ports
- Built-in SD slot supports MicroSD / SDHC / SDXC up to 128 GB
- Supports siren and audio expansion
- Supports video compresion H.264 / H.254+ / H.265 / H.265+
- Supports resolution 1920 x 1080
- Supports Smart Noise Supression
- Protection level: IP65
- Explosion-proof level: IK10



▪ Specification

Software features	
Wired network	10 M/100 M Self-adaptive Ethernet port
Hardware features	
Tamper-Proof	tamper alarm
Netowrk interface	1RJ45,10 M/100 M/1000 M self adaptive
Audio interface	1-ch Built-in Omnidirectional Microphone, Pickup Distance: 5 m 1-ch 3.5 mm Audio Interface for External Audio Input
PSTN	1
Bus	RS-485 1, Half-duplex
SD card	Standard Micro SD card Slot, Supports Micro SD/SDHC/SDXC Card, Max. 128G
Video	
Frame rate	25fps
Field angle	Horizontal: 128° Vertical: 85° Diagonal: 147°
Day/night switch mode	IR Cut Filter 10m IR
Electrical characteristics	
Power supply	12VDC or RJ45 PoE
Operation temperature	-40 °C to +60 °C (-40 °F to 140 °F)
Power consumption	≤ 24 W
Operation humidity	10% to 90%
General	
Dimension(WxHxD)	218 mm × 128 mm × 58 mm (8.58" × 5.04" × 2.28")
Installation method	Wall Mounting
Audio	
Sound pressure	110dB, Sound Can be Configured Separately
Audio input	1-ch Built-in Omnidirectional Microphone, Pickup Distance: 5 m 1-ch 3.5 mm Audio Interface for External Audio Input
Audio output	1-ch 3 W Build-in Loudspeaker 1-ch 3.5 mm Audio Interface for External Audio Output
Audio Compression	G.711
Audio compression code rate	16Kbps,64Kbps
Device management	
Alarm input	2
Camera	2 MP HD IR Camera
Alarm output	2
Report method	
Protocol	TCP/IP, RTSP, HIK-SIP,ONVIF
General	
Application scenario	Outdoor
Shell material	Metal

▪ Available Model

DS-PEA1-21, DS-PEA-SG

Distributed by

HIKVISION®

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Juan Andrés Granda Dávila

0301647277001

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision Turkey
T +90 [216]521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7652-2413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 [10] 0351172
sale.africa@hikvision.com

Hikvision France
T +33[0]1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikia.panfilov@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4432090
salesme@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Korea
T +82-[0]31-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com