

5860/5860R

Remote Annunciator

The 5860/R operates and programs Silent Knight® fire alarm control panels (FACPs). The 5860/R's keypad and display match the built-in annunciator of the FACP.

The remote annunciator connects to the control panel via the RS-485 system bus. When the system is in normal operation and has AC power, the Power LED is lit and all other LEDs are off. The other LEDs turn on as alarms, supervisories, troubles, system silenced, and AC power losses occur.

INSTALLATION

The 5860/R can be surface or flush mounted. Use the optional trim ring for surface mounts. When flush mounting, an electrical box is optional. If using an electrical box, use a 4S, single-gang, or double-gang box.

COMPATIBILITY

The 5860/R is compatible with the following Silent Knight FACPs:

- 6820/6820EVS
- 6808
- 6700
- 5820XL/5820XL-EVS
- 5808
- 5700



FEATURES AND BENEFITS

- UL listed. Complies with UL 864, 10th Edition; UL 2572, 2nd Edition; and NFPA 72
- 80-character backlit LCD display (4 lines with 20 characters on each line)
- Tactile/audible feedback
- RS-485 SBUS interface to panel
- Larger keypad buttons for system reset and silence
- Initiate and end fire drills with a single key press
- View current status by alarms, supervisories, or troubles
- On-board piezo sounder audibly indicates alarms, troubles, and supervisories
- Five status LEDs for; alarms, supervisory, trouble, silence and AC power indications
- Available in red or gray color
- Accepts user codes or fire fighter's key
- Support for simultaneous use of multiple 5860/Rs
- Wiring lengths up to 6000 ft. (1.83 km) from the FACP

5860/5860R TECHNICAL SPECIFICATIONS

PHYSICAL

Dimensions: 9.1" W x 7.4" H x 1.5" D
(23.1 cm W x 18.8 cm H x 3.8 cm D)

Shipping Weight: 2.8 lbs (1.3 kg)

Color: Red or Gray

ENVIRONMENTAL

Operating Temperature: 32° F to 120° F
(0° C to 49° C)

Humidity: 10% to 93% relative humidity
(noncondensing)

ELECTRICAL

Operating Voltage: 24 VDC

Standby Current: 20 mA

Alarm Current: 25 mA

Maximum Wiring Distance: 6,000 ft. (1.83 km) from FACP (depending on wire gauge and number of devices on the SBUS)

SYSTEM

Maximum No. of 5860/Rs per System:

- 8 for 5700 or 6700
- 12 for 5808 or 6808
- 16 for 5820XL/EVS or 6820/EVS

ORDERING INFORMATION

5860R: Red four line LCD Remote Annunciator with 20 characters per line.

5860: Gray four line LCD Remote Annunciator with 20 characters per line.

OPTIONAL ACCESSORIES

5860TR: Red Trim Ring for surface mounting.

5860TG: Gray Trim Ring for surface mounting.

STANDARDS AND CODES

The 5860/R complies with the following standards/codes:

- UL 864, 10th Edition: Standard for Control Units for Fire Alarm Systems
- UL 2572, 2nd Edition: Standard for Mass Notification Systems
- NFPA 72: National Fire Alarm and Signaling Code

AGENCY LISTINGS AND APPROVALS

- UL Listed
- FDNY - COA (TBD)

Honeywell® and Silent Knight® are registered trademarks of Honeywell International, Inc.

This document is not intended to be used for installation purposes. We try to keep our product information up-to-date and accurate. We cannot cover all specific applications or anticipate all requirements. All specifications are subject to change without notice.

Country of origin: U.S.A.

Honeywell Silent Knight

12 Clintonville Road
Northford, CT 06472-1610
203.484.7161
www.silentknight.com

350224 | 11/21
©2021 Honeywell International Inc.

