

DS-2CE16C0T-IT3F **1 MP Fixed Bullet Camera**



- HD 720p bullet camera
- EXIR 2.0: advanced infrared technology with 40 m IR distance
- Water and dust resistant (IP67)
- 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)

▪ Specification

Camera	
Image Sensor	1 MP CMOS
Max. Resolution	1296(H) × 732(V)
Min. Illumination	0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/25 s to 1/50,000 s; NTSC: 1/30 s to 1/50,000 s
Day & Night	IR Cut Filter
Angle Adjustment	Pan: 0 to 360°, Tilt: 0 to 180°, Rotation: 0 to 360°
Signal System	PAL/NTSC
Lens	
Lens Type	2.8 mm, 3.6 mm, 6 mm, 8 mm, 12 mm, and 16 mm fixed focal lens
Focal Length & FOV	70.9° (3.6 mm), 92° (2.8 mm), 56.7° (6 mm), 38.6° (8 mm), 27.5° (12 mm), 17.7° (16 mm)
Lens Mount	M12
Illuminator	
Supplement Light Type	IR
Supplement Light Range	Up to 40 m
Image	
Frame Rate	720p @ 25 fps/720p @ 30 fps
SNR	>62dB
Noise Reduction	2D DNR
Interface	
Video Output	1 HD analog output
General	
Power	12 V DC ± 15%, max. 4 W
Dimension	86.7 mm × 81.6 mm × 226 mm (3.4" × 3.2" × 8.9")
Weight	Approx. 700 g (1.54 lb.)
Operating Condition	-40 °C to 60 °C (-40 °F to 140 °F), humidity 90% or less (non-condensing)
Approval	
Protection	IP67

▪ Available Model

DS-2CE16C0T-IT3F(2.8mm)

DS-2CE16C0T-IT3F(3.6mm)

DS-2CE16C0T-IT3F(6mm)

DS-2CE16C0T-IT3F(8mm)

DS-2CE16C0T-IT3F(12mm)

- **Accessory**

- **Optional**

DS-1280ZJ-XS
Junction Box



Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision_Global



Hikvision
Corporate Channel



hikvisionhq